



BAUER

FOR A GREEN WORLD



EN



IRRIGATION

eco ProRain

WWW.BAUER-AT.COM

THE NEXT GENERATION OF BAUER EFFICIENCY

The new eco ProRain — the irrigation machine that is uncompromisingly focused on the essentials: quality, performance, and user convenience.

By concentrating on core functionalities, the eco ProRain is a cost-effective solution for farmers who prioritize quality and efficiency.

The Eco ProRain is available in pipe dimensions 110–620, 125–480, and 140–400.

FEATURES

- + In house made PE pipe
- + Chassis and turntable galvanized
- + 2-wheel chassis with fixed track width 2.0m
- + Removable jack
- + Revolving pipe reel
- + Hydraulic machine supports
- + 4 speed gear with mounted turbine
- + Automatic cart lift for wheel cart
- + Irrigation computer Ecostar 6000 as standard with 2 solar panels and 24Ah battery
- + Bauer PE-pipe winding device



CUSTOMER BENEFITS



SHORT PAYBACK PERIOD

The investment quickly pays for itself thanks to efficient performance and economic initial investment.



AFFORDABLE PURCHASE PRICE

Cost-effective investment offering excellent value for money.



USER-FRIENDLY OPERATION

Easy to use, allowing customers to operate the system with extensive technical training.



ADVANCED IRRIGATION MANAGEMENT

Enabled by high standard Irrigation Computer ECOSTAR 6000.



* All images for illustrative purposes only.

BAUER eco ProRain

PREMIUM ECOSTAR 6000 AS STANDARD

The new eco ProRain is equipped with the premium Ecostar 6000 irrigation computer from BAUER, designed to meet the latest standards in precision agriculture.

When it comes to efficient and sustainable water management, there's no room for compromise.

TOP HIGHLIGHTS OF ECOSTAR 6000

- + Touchscreen simplicity with button backup.
- + 12-program memory for tailored irrigation.
- + Water usage tracking and USB export.
- + Mobile control with error alerts.
- + SmartRain integration for advanced management.



eco ProRain

Designed for farms with straightforward field conditions around the world – the ideal solution for efficient and resource-conscious irrigation.

TECHNICAL SPECIFICATIONS

ProRain model	Type	PE pipe Ø (mm)	PE pipe length (m)	Max. strip length (m)	Turbine type	Connection Pressure (bar)	Total weight incl. water (kg)	Total weight without water (kg)
F50	110–620	110	620	675	TVR60	6,0 – 11,0	8.450	4.450
F50	125–480	125	480	535	TVR60	6,0 – 11,0	8.650	4.650
F50	140–400	140	400	455	TVR60	6,0 – 11,0	8.450	4.850



BAUER eco ProRain



WE GO BEYOND.



BAUER

FOR A GREEN WORLD

**Röhren- und Pumpenwerk
Bauer GmbH**

Kowaldstraße 2
A-8570 Voitsberg/Austria

bauer-at.com

Email
bauer@bauer-at.com

Phone
+43 3142 200-0

Instagram
@bauer.group