
 SLURRY AND LIQUID WASTE MANAGEMENT

PT16000

FOR XERION S-TRAC TYPE 784 | POLYESTER TANKS WITH A CAPACITY OF 16000 L

EN



PT 16000 REAR TANK

THE RIGHT SIZE FOR EVERY JOB

The polyester tank has a volume of 16000 l and is a handmade product by ECKART Maschinenbau GmbH. Thanks to many years of experience with polyester (GFRP), the highest level of quality can be achieved here.

Baffle plates are installed crosswise over width and length in the tank for improved strength, stability and weight distribution. The placement of the tank on the tractor results into better traction as well as a better HP/kg ratio.

The front unit with 10" PROFI docking arm, with integrated Power Fill System (PFS) can be rotated by 160°. With the help of the PFS, the tank can be filled extremely quickly.



STANDARD SPECIFICATION

- "Poly Tank", GFK tank for CLAAS XERION Saddle Trac 4200 Type 784
- Volume 16 m³
- RAL 7015 (CC-gray)
- Baffle plates 2x lengthwise und 1x crosswise
- 2x 600 mm x 600 mm manhole
- Tank is mounted on galvanized subframe
- Safety overflow left & right to the ground
- Vogelsang rotary pump VX186-390QD, 9000 l/min. at 600 rpm., inkl. Injection System
- Hydraulic pump driven via power hydraulic on the XERION
- Variable quantity / volume control
- BAUER Signo smart with 5.7"
- ISOBUS control via Signo Terminal and Müller Joystick possible
- Operation via F-Keys on the XERION possible
- Vogelsang dribble bar till 18 m possible (3.49 m transport width)
- Bomech trading shoe till 21 m possible (3.30 m transport width without support width)
- Applications systems till 6 m in the three-point possible
- 4x LED work lights in the back
- 30 l water tank



WE OFFER VARIOUS TYPES

- Frontunit: 10" pipes, 160° rotation, turbo filler, stone trap box, Vogelsang Rota-Cut RCX-58H with ACC, mounted to front linkage or XERION weight carrier frame, lights, connection tube from frontunit on sideways of cabin, 2x front work lights.

New features

- Optimized slurry flow
- Vogelsang cutting rotor for better flow
- Lower chance of cavitation
- Less pressure on the front axle thanks to weight reduction better weight balance
- Better view for the driver
- Storing frame for front unit

Options

- Vogelsang rotary pump VX186-520QD 12000 l/min.
- Camera incl. terminal
- BAUER Signo Pro 10,4"
- BAUER Signo Touch 8"
- BAUER Signo Touch 12"
- BAUER Signo ID - NIR System
- Track-Leader
- Section Control
- Part width shut off
- Special paint
- Frontunit storage frame
- Support carrier frame for frontunit
- Tube between tank and application system incl. couplings



Your dealer

BAUER Nord
Vertriebs- und Servicestützpunkt
Gersteinstraße 7
59227 Ahlen / Germany
T +49 2382 966 930
F +49 2382 966 930 - 5
M sales@bauer-at.com
W www.bauer-at.com

Contact:
Lukas Kuchheuser
Product Manager
+49 151 509 851 60
l.kuchheuser@bauer-at.com